NSN 4720-01-508-2731

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.188 inches

Tempurature Rating:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-508-2731

-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.343 inches
Minimum Inside Bending Radius:
2.000 inches
End Application:
Rq-4a
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:
Acid resistant and mildew resistant and fuel resistant
Vacuum In Torr:
50.8

NSN 4720-01-508-2731

Nonmetallic Hose Assembly - Page 2 of 2



nside Surface Condition:
Smooth
Measuring Method And Length:
6.375 inches working
Product Name:
Hose assembly
Thread Series Designator:
Jnjf 1st end
Specification Data:
96906-ms8005 government standard
Specification Or Standard:
C style or 4 size
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A542a0