Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-508-3052

Cross Castianal Shana
Cross Sectional Shape: Round
Thread Class:
2a 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
Between 0.625 inches and 0.667 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
Between 1.055 inches and 1.101 inches
Minimum Inside Bending Radius:
6.500 inches
End Application:
Ship; eafw misc parts
Connection Style:
External seat for gasket seal (boss) 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded external boss 2nd end
Thready Qty Per Inch (tpi):
12 2nd end
Burst Test Pressure:
2200.0 pounds per square inch
Layer Composition And Location:
Outer layer molded rubber, synthetic and 1st layer braided polyester cord and 2nd layer braided polyester cord
Maximum Operating Pressure:
550.0 pounds per square inch
Thread Size:
1.750 inches 1st end
Hydrostatic Test Pressure:
1100.0 pounds per square inch
Flow Angle:
90.0 degrees 1st end
Outer Covering Environmental Protection:
Abrasion resistant and oxidation resistant and light resistant and weatherproof
Criticality Code Justification:
Feat
Inside Surface Condition:
Smooth

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length:

34.540 inches

Product Name:

Dogleg hose assembly

Special Features:

Weapon system essential; assembly has 90 degree elbow 17.270 inch from each end

Media For Which Designed:

Hydraulic fluid single response

Thread Series Designator:

Un 2nd end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0