NSN 4720-01-508-3417

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-508-3417

Cross Sectional Shape:
Round
Thread Class:
2a 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
Between 0.625 inches and 0.667 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
Between 1.055 inches and 1.101 inches
Minimum Inside Bending Radius:
6.500 inches
End Application:
Ship; eafw misc parts
Connection Style:
External seat for gasket seal (boss) 1st end
End Connection Design:
Elbow 1st end
Connection Type:
Threaded external boss 1st end
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
2200.0 pounds per square inch
Layer Composition And Location:
Outer layer molded rubber, synthetic and 1st layer braided polyester cord and 2nd layer braided polyester cord
Maximum Operating Pressure:
550.0 pounds per square inch
Thread Size:
1.750 inches 1st end
Hydrostatic Test Pressure:
1100.0 pounds per square inch
Flow Angle:
90.0 degrees 1st end
Outer Covering Environmental Protection:
Abrasion resistant and oxidation resistant and light resistant and weatherproof
Criticality Code Justification:
Feat
Inside Surface Condition:

Smooth

NSN 4720-01-508-3417

A542a0

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length:
34.540 inches
Product Name:
Dogleg hose assembly
Special Features:
Weapon system essential; assembly has 90 degree elbow 17.270 inch from each end
Media For Which Designed:
Hydraulic fluid single response
Thread Series Designator:
Un 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: