NSN 4720-01-508-3747

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-508-3747

Cross Sectional Shape:
Round
Thread Class:
2a 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
Between 1.125 inches and 1.172 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
Between 1.469 inches and 1.531 inches
Minimum Inside Bending Radius:
9.000 inches
End Application:
Ship; eafw misc parts
Connection Style:
External seat for gasket seal (boss) 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external boss 1st end
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
1800.0 pounds per square inch
Layer Composition And Location:
Outer layer molded rubber, synthetic and 1st layer braided polyester cord and 2nd layer braided polyester cord
Maximum Operating Pressure:
450.0 pounds per square inch
Thread Size:
2.312 inches 1st end
Hydrostatic Test Pressure:
900.0 pounds per square inch
Outer Covering Environmental Protection:
Abrasion resistant and oxidation resistant and light resistant and weatherproof
Criticality Code Justification:
Feat
Inside Surface Condition:
Smooth
Measuring Method And Length:

43.800 inches

NSN 4720-01-508-3747

Fiig: A542a0

Nonmetallic Hose Assembly - Page 2 of 2



Product Name:
Dogleg hose assembly
Special Features:
Weapon system essential; assembly has 90 degree elbow 21.9 inch from each end
Media For Which Designed:
Hydraulic fluid single response
Thread Series Designator:
Un 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No