

View Online at <https://aerobasegroup.com/nsn/4720-01-508-3919>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.391 inches

Temperature Rating:

-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response

Outside Diameter:

0.765 inches

Minimum Inside Bending Radius:

2.880 inches

Hose Or Tubing Specification/std Data:

As1339, size 8-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).

End Application:

TANK-,A-BRA-MS,M

Connection Style:

Swivel nut, flareless 2nd end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting stainless steel all ends

Fitting Component And Surface Treatment:

Complete fitting passivate 1st end

Connection Type:

Threaded internal tube 1st end

Second End Relationship With First End:

Not identical

Burst Test Pressure:

14000.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

1st layer braided corrosion resistant steel wire err-100

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

0.750 inches 2nd end

Seat Angle:

12.0 degrees 2nd end

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Flow Angle:

45.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

45.000 inches working

Second End Swivel Action Capability:

Not included

Product Name:

Hose assembly, ptfe, cres reinforced, 3000 psi, 400 degrees f, straight to 45 degree flareless, lightweight

Special Features:

Abrasion sleeve shrink-on (fep)

Thread Series Designator:

Unjf 1st end

Specification Data:

81343-as116 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0