

View Online at <https://aerobasegroup.com/nsn/4720-01-508-3919>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.391 inches

**Temperature Rating:**

-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response

**Outside Diameter:**

0.765 inches

**Minimum Inside Bending Radius:**

2.880 inches

**Hose Or Tubing Specification/std Data:**

As1339, size 8-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).

**End Application:**

TANK-,A-BRA-MS,M

**Connection Style:**

Swivel nut, flareless 2nd end

**End Connection Design:**

Straight 1st end

**End Fitting Component And Material:**

Complete fitting stainless steel all ends

**Fitting Component And Surface Treatment:**

Complete fitting passivate 1st end

**Connection Type:**

Threaded internal tube 1st end

**Second End Relationship With First End:**

Not identical

**Burst Test Pressure:**

14000.0 pounds per square inch

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

1st layer braided corrosion resistant steel wire err-100

**Maximum Operating Pressure:**

3000.0 pounds per square inch

**Thread Size:**

0.750 inches 2nd end

**Seat Angle:**

12.0 degrees 2nd end

**Hydrostatic Test Pressure:**

6000.0 pounds per square inch

**Flow Angle:**

45.0 degrees 2nd end

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

45.000 inches working

**Second End Swivel Action Capability:**

Not included

**Product Name:**

Hose assembly, ptfe, cres reinforced, 3000 psi, 400 degrees f, straight to 45 degree flareless, lightweight

**Special Features:**

Abrasion sleeve shrink-on (fep)

**Thread Series Designator:**

Unjf 1st end

**Specification Data:**

81343-as116 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0