

View Online at <https://aerobasegroup.com/nsn/4720-01-508-4544>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.421 inches

Temperature Rating:

-55.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

Flange Thickness:

0.345 inches 1st end

Outside Diameter:

0.766 inches

Minimum Inside Bending Radius:

4.260 inches

Exterior Color:

Blue

End Application:

Engine diesel 36ss6v-am mdl 2894f01 6 cyl and engine diesel gen 36ssv-am mdl 2894f01 gen 6 cyl

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Reusable end fittings

Thready Qty Per Inch (tpi):

16 1st end

Burst Test Pressure:

8000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided polyester cord and 1st layer braided polyester cord and 2nd layer braided wire

Maximum Operating Pressure:

2000.0 pounds per square inch

Thread Size:

0.750 inches 1st end

Seat Angle:

37.0 degrees 1st end

Outer Covering Environmental Protection:

Salt water resistant and oil resistant

Vacuum In Torr:

28.0

Inside Surface Condition:

Smooth

Inside Diameter Hose Accommodated:

0.421 inches 1st end

Product Name:

Pre-lub hose assembly

Special Features:

Reuseable identical end fittings -- adapter, straight, tube to hose (p/n 259-4111-8 on nsn 4730-01-350-3754; hose, nonmetallic used is p/n ae372-8 on nsn 4720-00-717-1701; length of entire assembly is 60.000 in; end fitting length is 2.780 in each

Media For Which Designed:

Hydraulic fluid, phosphate-ester base and oil, lubricating, diester base single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0