Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-509-4436

С	ross Sectional Shape:
R	ound
Т	hread Class:
2	b 1st end
T	hread Direction:
R	ight-hand 1st end
In	side Diameter:
0.	.313 inches
T	empurature Rating:
-6	5.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response
0	utside Diameter:
0.	672 inches
Е	xterior Color:
G	ray
Е	nd Application:
Fi	ighter aircraft (f-18 e/f)
С	onnection Style:
s	wivel nut flare 1st end
Е	nd Connection Design:
	traight 1st end
	onnection Type:
	hreaded internal tube 1st end
в	urst Test Pressure:
90	000.0 pounds per square inch
	laximum Operating Pressure:
	000.0 pounds per square inch
	hread Size:
0	.562 inches 1st end
-	eat Angle:
	7.0 degrees 1st end
	outer Covering Environmental Protection:
	il resistant
-	nside Surface Condition:
	mooth
-	leasuring Method And Length:
	.625 inches excluding end fittings
	ledia For Which Designed:
	uel/oil, hydrocarbon single response
	hread Series Designator:
-	nf 1st end
S	helf Life:

N/a

NSN 4720-01-509-4436

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0