Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-509-6465

C	cross Sectional Shape:
R	lound
Т	hread Class:
3	b 1st end
Т	hread Direction:
R	light-hand 1st end
Ir	nside Diameter:
1	.000 inches
Т	empurature Rating:
-{	54.0 degrees celsius single response and 204.0 degrees celsius single response
C	Outside Diameter:
1	.282 inches
N	linimum Inside Bending Radius:
5	.000 inches
С	connection Style:
Ν	lut assembly with gasket 1st end
E	nd Connection Design:
E	lbow 1st end
С	connection Type:
Т	hreaded internal hose 1st end
Т	hready Qty Per Inch (tpi):
1	2 1st end
B	Burst Test Pressure:
4	00.0 pounds per square inch
N	laximum Operating Pressure:
2	00.0 pounds per square inch
Т	hread Size:
1	.312 inches 1st end
F	low Angle:
4	5.0 degrees 1st end
Ir	nside Surface Condition:
С	Convoluted
N	leasuring Method And Length:
1	9.000 inches
Т	hread Series Designator:
ι	Inj 1st end
S	helf Life:
Ν	l/a
U	nit Of Measure:
D	emilitarization:
Ν	lo

## NSN 4720-01-509-6465

Nonmetallic Hose Assembly - Page 2 of 2

**Fiig:** A542a0

