. **.** Non



View Online at https://aerobasegroup.com/nsn/4720-01-510-2023 Cross Sectional Shape: Round Thread Class: 2b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.375 inches Tempurature Rating: 3.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.350 inches Minimun Inside Bending Radius: 3.000 inches Exterior Color: Green or red Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Thread Qty Per Inch (tpi): View of the State of S
Round Thread Class: 2b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.375 inches Tempurature Rating: 33.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.750 inches Minimum Inside Bending Radius: 3.000 inches Exterior Color: Green or red Connection Style: Swivel nut flare 1st end Extraiget 1st end Connection Tppe: Threaded internal tube 1st end Threaded internal tube 1st end Threaded internal tube 1st end
Thread Class: 2b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.375 inches Tempurature Rating: 33.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.750 inches Minimum Inside Bending Radius: 3.000 inches Exterior Color: Green or red Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Threaded internal tube 1st end
2b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.375 inches Tempurature Rating: 33.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.750 inches Minimum Inside Bending Radius: 3.000 inches Exterior Color: Green or red Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end
Thread Direction: Right-hand 1st end Inside Diameter: 0.375 inches Tempurature Rating: 33.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.750 inches Minimum Inside Bending Radius: 3.000 inches Exterior Color: Green or red Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Threaded internal tube 1st end
Right-hand 1st end Inside Diameter: 0.375 inches Tempurature Rating: 33.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.750 inches 0.750 inches Minimur Inside Bending Radius: 3.000 inches Exterior Color: Green or red Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Threaded internal tube 1st end
Inside Diameter: 0.375 inches Tempurature Rating: 33.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.750 inches Minimun Inside Bending Radius: 3.000 inches Exterior Color: Green or red Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Threaded internal tube 1st end
0.375 inches Tempurature Rating: 33.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.750 inches Minimum Inside Bending Radius: 3.000 inches Exterior Color: Green or red Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi):
Tempurature Rating: 33.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.750 inches Minimum Inside Bending Radius: 3.000 inches Exterior Color: Green or red Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi):
33.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.750 inches Minimum Inside Bending Radius: 3.000 inches Exterior Color: Green or red Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi):
Outside Diameter: 0.750 inches Minimum Inside Bending Radius: 3.000 inches Exterior Color: Green or red Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi):
0.750 inches Minimum Inside Bending Radius: 3.000 inches Exterior Color: Green or red Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi):
Minimum Inside Bending Radius: 3.000 inches Exterior Color: Green or red Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi):
3.000 inches Exterior Color: Green or red Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi):
Exterior Color: Green or red Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi):
Green or red Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi):
Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi):
Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi):
End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi):
Straight 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi):
Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi):
Threaded internal tube 1st end Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi):
18 1st end
Burst Test Pressure:
800.0 pounds per square inch
Layer Composition And Location:
Outer layer molded rubber, ethylene propylene and 1st layer braided fabric and 2nd layer braided fabric
Maximum Operating Pressure:
200.0 pounds per square inch
Thread Size:
0.5625 inches 1st end
Seat Angle:
37.0 degrees 1st end
Inside Surface Condition:
Smooth
Measuring Method And Length:
19.750 inches working and 20.250 inches working
Product Name:
Hose assembly, rubber

Thread Series Designator:

Unf 1st end

NSN 4720-01-510-2023

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

