## NSN 4720-01-510-2029

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-510-2029

| Cross Sectional Shape:  |
|---|
| Round   |
| Thread Class:   |
| 2b 1st end  |
| Thread Direction:   |
| Right-hand 1st end  |
| Inside Diameter:  |
| 0.500 inches  |
| Tempurature Rating:   |
| 33.0 degrees fahrenheit and 200.0 degrees fahrenheit single response                                    |
| Outside Diameter:   |
| 0.875 inches  |
| Minimum Inside Bending Radius:  |
| 3.000 inches  |
| Exterior Color:   |
| Green or red  |
| Connection Style:   |
| Swivel nut flare 1st end  |
| End Connection Design:  |
| Straight 1st end  |
| Connection Type:  |
| Threaded internal tube 1st end  |
| Thready Qty Per Inch (tpi):   |
| 16 1st end  |
| Burst Test Pressure:  |
| 800.0 pounds per square inch  |
| Layer Composition And Location:   |
| Outer layer molded rubber, ethylene propylene and 1st layer braided fabric and 2nd layer braided fabric |
| Maximum Operating Pressure:   |
| 200.0 pounds per square inch  |
| Thread Size:  |
| 0.750 inches 1st end  |
| Seat Angle:   |
| 37.0 degrees 1st end  |
| Inside Surface Condition:   |
| Smooth  |
| Measuring Method And Length:  |
| 19.750 inches working and 20.250 inches working   |
| Product Name:   |
| Hose assembly, rubber   |
| Thread Series Designator:   |

Unf 1st end

## NSN 4720-01-510-2029

Nonmetallic Hose Assembly - Page 2 of 2



| _ |   |    | • |    |    |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
|   |   |    |   |    |    |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0