NSN 4720-01-510-4298

Cross Sectional Shape:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-510-4298

Round					
Thread Class:					
3b 1st end					
Thread Direction:					
Right-hand 1st end					
Inside Diameter:					
0.212 inches					
Tempurature Rating:					
-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response					
Outside Diameter:					
Between 0.360 inches and 0.390 inches					
Minimum Inside Bending Radius:					
1.500 inches					
End Application:					
2350-01-305-0028					
Connection Style:					
Swivel nut flare 2nd end					
End Connection Design:					
Straight 1st end					
Connection Type:					
Threaded internal tube 1st end					
Burst Test Pressure:					
16000.0 pounds per square inch					
Maximum Operating Pressure:					
3000.0 pounds per square inch					
Thread Size:					
0.4375 inches 2nd end					
Seat Angle:					
37.0 degrees 2nd end					
Hydrostatic Test Pressure:					
6000.0 pounds per square inch					
Flow Angle:					
90.0 degrees 2nd end					
Inside Surface Condition:					
Smooth					
Measuring Method And Length:					
36.000 inches working					
Thread Series Designator:					
Unjf 1st end					
Specification Data:					
81434-as155 professional/industrial association standard					

NSN 4720-01-510-4298

Nonmetallic Hose Assembly - Page 2 of 2



_				
c	hο	.1+		ife:
J	116		_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0