NSN 4720-01-510-5608

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-510-5608
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
Between 0.171 inches and 0.205 inches
Tempurature Rating:
-54.0 degrees celsius and 204.0 degrees celsius single response
Outside Diameter:
Between 0.278 inches and 0.324 inches
Minimum Inside Bending Radius:
2.000 inches
End Application:
2320-00-104-4703
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
18 1st end
Burst Test Pressure:
10000.0 pounds per square inch
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.625 inches 1st end
Seat Angle:
45.0 degrees 1st end
Hydrostatic Test Pressure:
5000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
445.0 millimeters and 469.0 millimeters
Outside Diameter Tube Accommodated:
0.375 inches 1st end
Thread Series Designator:

Unf 1st end

NSN 4720-01-510-5608

Nonmetallic Hose Assembly - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0