

View Online at <https://aerobasegroup.com/nsn/4720-01-510-5608>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

Between 0.171 inches and 0.205 inches

Temperature Rating:

-54.0 degrees celsius and 204.0 degrees celsius single response

Outside Diameter:

Between 0.278 inches and 0.324 inches

Minimum Inside Bending Radius:

2.000 inches

End Application:

2320-00-104-4703

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

18 1st end

Burst Test Pressure:

10000.0 pounds per square inch

Maximum Operating Pressure:

1500.0 pounds per square inch

Thread Size:

0.625 inches 1st end

Seat Angle:

45.0 degrees 1st end

Hydrostatic Test Pressure:

5000.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

445.0 millimeters and 469.0 millimeters

Outside Diameter Tube Accommodated:

0.375 inches 1st end

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0