

View Online at <https://aerobasegroup.com/nsn/4720-01-511-0374>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.375 inches

Outside Diameter:

Between 0.594 inches and 0.656 inches

Minimum Inside Bending Radius:

3.000 inches

End Application:

FMTV-NS-N23-2001

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

18 1st end

Burst Test Pressure:

1000.0 pounds per square inch

Maximum Operating Pressure:

250.0 pounds per square inch

Thread Size:

0.625 inches 1st end

Seat Angle:

45.0 degrees 1st end

Hydrostatic Test Pressure:

500.0 pounds per square inch

Outer Covering Environmental Protection:

Fuel resistant and oil resistant and mildew resistant and vibration resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

2945.4 millimeters

Product Name:

Hose assembly, nonmetallic-pneumatic

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0