

View Online at <https://aerobasegroup.com/nsn/4720-01-511-5993>

Cross Sectional Shape:

Round

Inside Diameter:

0.500 inches

Tempurature Rating:

450.0 degrees fahrenheit single response

Outside Diameter:

0.585 inches

Minimum Inside Bending Radius:

4.625 inches

Angle Between Rigid Elbow Fittings In Deg:

320.0

End Application:

Sh-2g seasprite helicopter

End Connection Design:

Elbow 2nd end

Burst Test Pressure:

6000.0 pounds per square inch

Maximum Operating Pressure:

1500.0 pounds per square inch

Hydrostatic Test Pressure:

3000.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Measuring Method And Length:

17.500 inches working

Special Features:

Burst pressure 8, 000 psi min at room temperature, 6, 000 psi min at high temperature; fitting material corrosion resistant steel nut or flange socket and nipple; color code drain

Special Markings:

Kaman part number, manufacturer's part number, manufacturer's name and date of assembly shall be permanently attached to the hose assembly

Test Data Document:

81349-mil-h-25579 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Fsc Application Data:

Nha kpd 878301

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig: