

View Online at <https://aerobasegroup.com/nsn/4720-01-511-5997>

Cross Sectional Shape:

Round

Inside Diameter:

0.250 inches

Temperature Rating:

450.0 degrees fahrenheit single response

Outside Diameter:

0.343 inches

Minimum Inside Bending Radius:

2.000 inches

End Application:

Sh-2g seasprite helicopter

End Connection Design:

Straight 1st end

Burst Test Pressure:

7000.0 pounds per square inch

Maximum Operating Pressure:

1500.0 pounds per square inch

Hydrostatic Test Pressure:

3000.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Measuring Method And Length:

20.750 inches working

Special Features:

Burst pressure 12, 000 psi min at room temperature, 7, 000 psi min at high temperature; fitting material corrosion resistant steel nut or flange socket and nipple; color code drain

Special Markings:

Kaman part number, manufacturer's part number, manufacturer's name and date of assembly shall be permanently attached to the hose assembly

Test Data Document:

81349-mil-h-25579 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Fsc Application Data:

Nha kpd 870306

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0