

View Online at <https://aerobasegroup.com/nsn/4720-01-511-6000>

Cross Sectional Shape:

Round

Inside Diameter:

0.625 inches

Temperature Rating:

450.0 degrees fahrenheit single response

Outside Diameter:

0.687 inches

Minimum Inside Bending Radius:

5.500 inches

End Application:

Sh-2g seasprite helicopter

End Connection Design:

Straight 2nd end

Burst Test Pressure:

5500.0 pounds per square inch

Maximum Operating Pressure:

1500.0 pounds per square inch

Hydrostatic Test Pressure:

3000.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Measuring Method And Length:

47.000 inches working

Special Features:

Burst pressure 7, 000 psi min at room temperature, 5, 500 psi min at high temperature; color code lube

Special Markings:

Kaman part number, manufacturer's part number, manufacturer's name and date of assembly shall be permanently attached to the hose assembly

Test Data Document:

81349-mil-h-25579 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Fsc Application Data:

Nha kpd 870306

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0