

View Online at <https://aerobasegroup.com/nsn/4720-01-512-6910>

Cross Sectional Shape:

Round

Inside Diameter:

Between 2.000 inches and 2.031 inches

Temperature Rating:

-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response

Flange Thickness:

1.440 inches 1st end

Outside Diameter:

Between 2.661 inches and 2.693 inches

Minimum Inside Bending Radius:

25.000 inches

Hose Or Tubing Specification/std Data:

Mil-h-24135/9, size 32 - 81349 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

First End Fitting Specification/std Data:

Sae j518 code 62 - 81343 standard (includes industry or association standards, individual manufactureer standards, etc.).

Center To Center Distance Between Bolt Holes Along Width:

1.750 inches 1st end

Center To Center Distance Between Bolt Holes Along Length:

3.812 inches 1st end

Bolt Hole Quantity:

4 1st end

Flange Length:

5.250 inches 1st end

End Application:

Hydraulic power unit

Flange Width:

4.400 inches 1st end

Connection Style:

Plain swivel w/ gasket groove 1st end

Bolt Hole Diameter:

0.781 inches 1st end

End Flange Construction:

Split 1st end

End Connection Design:

Elbow 1st end

Connection Type:

Plain face flange 1st end

Second End Relationship With First End:

Identical

Burst Test Pressure:

12000.0 pounds per square inch

Layer Composition And Location:

1st layer spirally laid steel wire err-100

Maximum Operating Pressure:

3000.0 pounds per square inch

Flow Angle:

90.0 degrees 1st end

Outer Covering Environmental Protection:

Hydraulic solution resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

72.000 inches

Flange Style:

Double oval (sae split type flange) 1st end

Special Features:

Inner conveying tube material-rubber, synthetic

Media For Which Designed:

Hydraulic fluid single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-24135 spec.