Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-513-5007

Round

Thread Class:

2a 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.500 inches

Tempurature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

0.890 inches

Minimum Inside Bending Radius:

4.000 inches

Exterior Color:

Black

End Application:

Operator mnl

Connection Style:

External seat for gasket seal (boss) 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded external boss 1st end

Features Provided:

Perforated outer cover

Burst Test Pressure:

14000.0 pounds per square inch

Layer Composition And Location:

1st layer braided synthetic cord and outer layer molded polyurethane

Maximum Operating Pressure:

3500.0 pounds per square inch

Thread Size:

0.750 inches 1st end

Hydrostatic Test Pressure:

7000.0 pounds per square inch

Outer Covering Environmental Protection:

Hydraulic solution resistant and weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

39.000 inches

Nonmetallic Hose Assembly - Page 2 of 2

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

