Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-513-5427

| Cross Sectional Shaney |
|---|
| Cross Sectional Shape: |
| Round |
| Thread Class: |
| 2b 1st end |
| Inside Diameter: |
| 0.120 inches |
| Tempurature Rating: |
| -45.6 degrees celsius single response and 165.0 degrees celsius single response |
| Outside Diameter: |
| 0.230 inches |
| End Application: |
| 1430-01-418-4396 radar set, semitrailer mounted |
| Connection Style: |
| Swivel nut, compression 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Thready Qty Per Inch (tpi): |
| 24 1st end |
| Burst Test Pressure: |
| 400.0 pounds per square inch |
| Layer Composition And Location: |
| Outer layer braided corrosion resistant steel wire |
| Maximum Operating Pressure: |
| 200.0 pounds per square inch |
| Thread Size: |
| 0.375 inches 1st end |
| Outer Covering Environmental Protection: |
| Corrosion resistant |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 17.660 inches and 17.821 inches |
| Special Features: |
| End fittings have dry film lube applied; media foe which designed: transformer oil iaw astm d3487 |
| Supplementary Features: |
| Hex nut .50 across flats |
| Thread Series Designator: |
| Unf 1st end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| |

NSN 4720-01-513-5427

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0