

View Online at <https://aerobasegroup.com/nsn/4720-01-513-5866>

**Minimum Inside Bending Radius:**

54.000 inches

**End Application:**

Misc parts list for ac-cw, piping cw pmp rtn to r134a ac unit engine room, virginia class ssn

**Features Provided:**

Reusable end fittings

**Burst Test Pressure:**

1200.0 pounds per square inch

**Layer Composition And Location:**

1st layer spirally wrapped fabric and outer layer rubber composition

**Maximum Operating Pressure:**

300.0 pounds per square inch

**Measuring Method And Length:**

35.000 feet excluding end fittings and 36.000 feet excluding end fittings

**Product Name:**

Hose assembly, 90, flg

**Special Features:**

Assy is low pressure hose assembly, 90, flg, 8.000nps, 46.100x46.700 (p/n f226) and includes 1 hose (-128), syn rbr, 8.000 i.D. X 8.940 o.D., 300 psi, 35 in long (p/n f226-1), 1 hose (-128), syn rbr, 8.000 o.D. X 8.940 o.D., 300 psi, 36 in long (p/n f226-2), 1 elbow, 90 deg, hose x flg -128 hose, fig 2, ty-bii (p/n f226-3), 1 elbow, 90 deg, hose x hose -128 hose, fig 5, ty e (p/n f226-4), 1 fitting, str end, hose x flg -128 hose x 8.000nps, fig 5, ty-aii (p/n f226-5), 1 tag assembly, hose, 8.000 to 10.000 diameter per 2633-225-01 (p/n f226-6)

**Media For Which Designed:**

Water single response

**Specification Data:**

81349-mil-h-24136/1 government specification and 81349-mil-f-24787 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0