

View Online at <https://aerobasegroup.com/nsn/4720-01-513-6371>

Minimum Inside Bending Radius:

42.000 inches

End Application:

Misc parts list for ac-cw, piping cw pmp rtn to r134a ac unit engine room, virginia class ssn

Features Provided:

Reusable end fittings

Burst Test Pressure:

1200.0 pounds per square inch

Layer Composition And Location:

1st layer spirally wrapped fabric and outer layer rubber composition

Maximum Operating Pressure:

300.0 pounds per square inch

Measuring Method And Length:

33.000 feet excluding end fittings

Product Name:

Hose assembly, straight, flg

Special Features:

Assy is low pressure hose assembly, straight, flg, 6.000nps, 38.000lg (p/n f240) and includes 1 hose (-96), syn rbr, 6.000 i.D. X 6.880 o.D., 300 psi, 33 in long (p/n f240-1), 2 fittings, str end, hose x flg (-96) hose x 6.000nps, fig 1, ty-aii (p/n f240-2), 1 tag assembly, hose, 4.000 to 8.000 per 2633-225-01, sheet 4-5 (p/n f240-3)

Media For Which Designed:

Water single response

Specification Data:

81349-mil-h-24136/1 government specification and 81349-mil-f-24787 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0