Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-513-6627

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.500 inches
End Application:
Ship, valves
Connection Style:
Swivel nut, gasket seal 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal hose 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
1600.0 pounds per square inch
Layer Composition And Location:
1st layer molded rubber and outer layer woven cotton cord
Maximum Operating Pressure:
150.0 pounds per square inch
Thread Size:
1.500 inches 1st end
Outer Covering Environmental Protection:
Fuel resistant and salt water resistant
Criticality Code Justification:
Feat
Inside Surface Condition:
Smooth
Measuring Method And Length:
50.0 feet
Special Features:
Weapon system essential; liner galvanized steel; includes rubber washers
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Npsh 1st end
Shelf Life:
N/a
Unit Of Measure:

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

