Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-513-6905

Cr	ross Sectional Shape:
Ro	bund
Tŀ	aread Direction:
Ri	ght-hand 1st end
In	side Diameter:
0.	750 inches
Er	nd Application:
Sh	ip; valve
Co	onnection Style:
Sv	vivel nut, gasket seal 1st end
Er	nd Connection Design:
St	raight 1st end
Co	onnection Type:
Th	readed internal hose 1st end
Вι	urst Test Pressure:
60	0.0 pounds per square inch
La	yer Composition And Location:
1s	t layer braided cotton cord and outer layer woven cotton cord
Ну	/drostatic Test Pressure:
30	0.0 pounds per square inch
0	uter Covering Environmental Protection:
Oz	zone resistant and weatherproof
Cr	iticality Code Justification:
Fe	pat
In	side Surface Condition:
Sr	nooth
M	easuring Method And Length:
25	0.0 feet
Sp	pecial Features:
W	eapon system essential; includes two rubber washers
M	edia For Which Designed:
W	ater, drinking single response
Th	aread Series Designator:
Np	osh 1st end
Sł	nelf Life:
N/	a
Ur	nit Of Measure:
De	emilitarization:
No	
Fi	ig:
A5	542a0