

View Online at <https://aerobasegroup.com/nsn/4720-01-513-7147>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.421 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

0.768 inches

Minimum Inside Bending Radius:

4.620 inches

End Application:

Ship; valves

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

14 1st end

Burst Test Pressure:

2500.0 pounds per square inch

Layer Composition And Location:

Outer layer molded rubber, synthetic and 1st layer braided polyester cord and 2nd layer braided polyester cord

Maximum Operating Pressure:

625.0 pounds per square inch

Thread Size:

0.875 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

1200.0 pounds per square inch

Outer Covering Environmental Protection:

Abrasion resistant and weatherproof and oxidation resistant and light resistant

Criticality Code Justification:

Feat

Inside Surface Condition:

Smooth

Measuring Method And Length:

15.0 feet

Special Features:

Weapon system essential

Media For Which Designed:

Water, drinking single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0