

View Online at <https://aerobasegroup.com/nsn/4720-01-513-7712>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.375 inches

Temperature Rating:

-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

Outside Diameter:

0.630 inches

Minimum Inside Bending Radius:

3.000 inches

Exterior Color:

Black

End Application:

Pwp mod 1 cmu assembly

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Reusable end fittings

Thready Qty Per Inch (tpi):

18 1st end

Burst Test Pressure:

1200.0 pounds per square inch

Maximum Operating Pressure:

300.0 pounds per square inch

Thread Size:

0.582 inches 1st end

Seat Angle:

37.0 degrees 1st end

Outer Covering Environmental Protection:

Fire resistant

Inside Surface Condition:

Convuluted

Measuring Method And Length:

84.000 inches

Outside Diameter Tube Accommodated:

0.375 inches 1st end

Special Features:

Could fabricate from 4730-00-203-3558 and 4720-01-280-2306. Piece 31 used on door air cylinder front; piece 32 used on door air cylinder, rear; piece 33 used on ram air cylinder bottom; piece 34 used on ram air cylinder top.; layer composition and location 1st layer molded rubber, synthetic 2nd layer braided textile yarn and fire resistant fiber cover

Media For Which Designed:

Air single response

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0