

View Online at <https://aerobasegroup.com/nsn/4720-01-513-9231>

**Cross Sectional Shape:**

Round

**Thread Class:**

2b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.410 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

**Outside Diameter:**

0.760 inches

**Minimum Inside Bending Radius:**

1.750 inches

**Exterior Color:**

Blue

**End Application:**

Pwp mod 1 cmu assembly

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Reusable end fittings

**Thready Qty Per Inch (tpi):**

16 1st end

**Burst Test Pressure:**

5000.0 pounds per square inch

**Layer Composition And Location:**

3rd layer molded polyurethane and 2nd layer braided polyamide cord and 1st layer braided steel wire

**Maximum Operating Pressure:**

1250.0 pounds per square inch

**Thread Size:**

0.750 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Outer Covering Environmental Protection:**

Fire resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

36.250 inches excluding end fittings

**Special Features:**

Could be fabricated from 4730-00-203-3558 and 4720-01-280-2306; this hose assembly is for used as door return hose assembly.

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Thread Series Designator:**

Un 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0