NSN 4720-01-515-7080

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-515-7080

| Cross Sectional Shape: |
|--|
| Round |
| Thread Class: |
| 2b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.188 inches |
| Tempurature Rating: |
| -65.0 degrees fahrenheit and 160.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.516 inches |
| Minimum Inside Bending Radius: |
| 3.000 inches |
| Exterior Color: |
| Black |
| End Application: |
| Munitions handling loading lift truck 7000 lbs mj |
| Connection Style: |
| Swivel nut flare 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Features Provided: |
| Reusable end fittings |
| Burst Test Pressure: |
| 12000.0 pounds per square inch |
| Layer Composition And Location: |
| Outer layer rubber impregnated braided fabric and 1st layer braided fiber and 2nd layer braided steel wire |
| Maximum Operating Pressure: |
| 3000.0 pounds per square inch |
| Thread Size: |
| 0.438 inches 1st end |
| Seat Angle: |
| 37.0 degrees 1st end |
| Hydrostatic Test Pressure: |
| 6000.0 pounds per square inch |
| Outer Covering Environmental Protection: |
| Mildew resistant and oil resistant |
| Vacuum In Torr: |

50.8

NSN 4720-01-515-7080

Nonmetallic Hose Assembly - Page 2 of 2



| Inside Surface Condition: |
|---------------------------------------|
| Smooth |
| Measuring Method And Length: |
| 35.750 inches |
| Media For Which Designed: |
| Fuel/oil, hydrocarbon single response |
| Thread Series Designator: |
| Unf 1st end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A542a0