

View Online at <https://aerobasegroup.com/nsn/4720-01-515-9763>

**Cross Sectional Shape:**

Round

**Thread Class:**

2b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.406 inches

**Temperature Rating:**

-65.0 degrees fahrenheit single response and 160.0 degrees fahrenheit single response

**Outside Diameter:**

0.766 inches

**Minimum Inside Bending Radius:**

4.625 inches

**Exterior Color:**

Black

**Hose Or Tubing Specification/std Data:**

Mil-h-8794 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**End Application:**

Munitions handling loading lift truck 7000 lbs mj

**Connection Style:**

Swivel nut flare 2nd end

**End Connection Design:**

Straight 1st end

**End Fitting Component And Material:**

Complete fitting steel all ends

**Fitting Component And Surface Treatment:**

Complete fitting cadmium 1st end

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Reusable end fittings

**Second End Relationship With First End:**

Not identical

**Burst Test Pressure:**

8000.0 pounds per square inch

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

Outer layer rubber impregnated braided fabric err-100

**Maximum Operating Pressure:**

2000.0 pounds per square inch

**Thread Size:**

0.750 inches 2nd end

**Seat Angle:**

37.0 degrees 2nd end

**Hydrostatic Test Pressure:**

4000.0 pounds per square inch

**Flow Angle:**

90.0 degrees 2nd end

**Outer Covering Environmental Protection:**

Mildew resistant and oil resistant

**Vacuum In Torr:**

50.8

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

66.000 inches

**Second End Swivel Action Capability:**

Not included

**Special Features:**

Inner conveying tube material-rubber, synthetic

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Thread Series Designator:**

Unf 2nd end

**Specification Data:**

Mil-h-8794 professional/industrial association specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0

**Mil-std (military Standard):**

Mil-h-8794 spec.