NSN 4720-01-516-6535

Cross Sectional Shape:

Inside Diameter: 0.602 inches

Tempurature Rating:

Flange Thickness: 0.100 inches 1st end

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-516-6535

-67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response

| Outside Diameter: |
|--|
| 1.140 inches |
| Minimum Inside Bending Radius: |
| 7.750 inches |
| Flange Outside Diameter: |
| 1.200 inches 1st end |
| End Application: |
| Starboard console |
| Connection Style: |
| Plain 1st end |
| End Flange Construction: |
| Solid 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Plain face flange 1st end |
| Features Provided: |
| Nuts drilled for lockwire |
| Burst Test Pressure: |
| 12000.0 pounds per square inch |
| Layer Composition And Location: |
| Outer layer braided corrosion resistant steel wire |
| Maximum Operating Pressure: |
| 3000.0 pounds per square inch |
| Hydrostatic Test Pressure: |
| 6000.0 pounds per square inch |
| Flow Angle: |
| 90.0 degrees 2nd end |
| Criticality Code Justification: |
| Feat |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 72.000 inches working |
| |
| |

NSN 4720-01-516-6535

Nonmetallic Hose Assembly - Page 2 of 2



| Flange Style: |
|--|
| Round w/ out bolt holes 1st end |
| Special Features: |
| Weapon system essential; union nuts with lockwire holes; 1.25-12 unf 2b threads; seals to o'ring face seal union threadpiece |
| Media For Which Designed: |
| Refrigerant 13 single response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

Mil-std (military Standard): Mil-h-38360 spec.

A542a0