NSN 4720-01-516-6572

Maximum Operating Pressure: 2500.0 pounds per square inch

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-516-6572

Cross Sectional Shape:
Round
Inside Diameter:
0.750 inches
Tempurature Rating:
-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response
Flange Thickness:
0.100 inches 1st end
Outside Diameter:
1.300 inches
Minimum Inside Bending Radius:
9.000 inches
Hose Or Tubing Specification/std Data:
Sae j517 100r8 standard (includes industry or association standards, individual manufactureer standards, etc.).
Flange Outside Diameter:
1.200 inches 1st end
End Application:
Starboard console
Connection Style:
Plain 1st end
End Flange Construction:
Solid 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting stainless steel all ends
Fitting Component And Surface Treatment:
Complete fitting passivate 1st end
Connection Type:
Plain face flange 1st end
Features Provided:
Nuts drilled for lockwire
Second End Relationship With First End:
Identical
Burst Test Pressure:
9000.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
Outer layer molded plastic err-100

NSN 4720-01-516-6572

Nonmetallic Hose Assembly - Page 2 of 2



Outer Covering Environmental Protection:	
Weatherproof	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
27.500 inches working	
Flange Style:	
Round w/ out bolt holes 1st end	
Special Features:	
Weapon system essential; 1.25-12 unf 2b threads; seals to o'ring face seal union threadpiece	
Media For Which Designed:	
Fuel/oil, hydrocarbon single response	
Specification Data:	
Sae j517 100r8 national std/spec	
Shelf Life:	
N/a	
Unit Of Measure:	
-	
Demilitarization:	
No	
Fiig:	
A542a0	