

View Online at <https://aerobasegroup.com/nsn/4720-01-516-8063>

Cross Sectional Shape:

Round

Inside Diameter:

0.500 inches

Outside Diameter:

0.890 inches

Minimum Inside Bending Radius:

7.000 inches

Hose Or Tubing Specification/std Data:

Sae100r9 type at standard (includes industry or association standards, individual manufactureer standards, etc.).

First End Fitting Specification/std Data:

Saej516 table 4i-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).

End Application:

Abtts hydraulic system

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting stainless steel all ends

Connection Type:

Threaded internal tube 1st end

Features Provided:

Nonskive

Second End Relationship With First End:

Identical

Burst Test Pressure:

18000.0 pounds per square inch

Layer Composition And Location:

1st layer spirally laid steel wire err-100

Maximum Operating Pressure:

4000.0 pounds per square inch

Seat Angle:

37.0 degrees 1st end and 45.0 degrees 1st end

Inside Surface Condition:

Smooth

Measuring Method And Length:

37.000 inches working

Special Features:

Inner conveying tube material-rubber, synthetic

Media For Which Designed:

Hydraulic fluid single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0