Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-517-5989

Cross Sect	ional Shape:
Round	
Thread Cla	SS:
3b 1st end	
Thread Dire	ection:
Right-hand	1st end
Inside Dian	neter:
0.298 inche	S
Tempuratu	re Rating:
-65.0 degre	es fahrenheit single response and 400.0 degrees fahrenheit single response
Outside Dia	ameter:
0.656 inche	S
Minimum Iı	nside Bending Radius:
5.000 inche	S
End Applic	ation:
Aircraft, har	rier av-8b
Connectior	n Style:
Swivel nut f	are 1st end
End Conne	ction Design:
Straight 1st	end
Connection	а Туре:
Threaded in	ternal tube 1st end
Burst Test	Pressure:
10500.0 pot	unds per square inch
Layer Com	position And Location:
Outer layer	braided corrosion resistant steel wire
Maximum (Operating Pressure:
3000.0 pour	nds per square inch
Thread Size	e:
0.562 inche	s 1st end
Seat Angle	:
37.0 degree	s 1st end
Hydrostatio	: Test Pressure:
6000.0 pour	nds per square inch
Outer Cove	ring Environmental Protection:
Corrosion re	esistant
Inside Surf	ace Condition:
Smooth	
Measuring	Method And Length:
17.500 inch	es working
Thread Ser	ies Designator:
Unjf 1st end	

Nonmetallic Hose Assembly - Page 2 of 2



Specification Data:

81349-mil-h-38360 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0