Nonmetallic Hose Assembly - Page 1 of 2





**Cross Sectional Shape:** Round **Thread Class:** 3b 1st end Thread Direction: Right-hand 1st end **Inside Diameter:** 0.485 inches **Tempurature Rating:** 204.0 degrees celsius single response **Outside Diameter:** 0.715 inches **Minimum Inside Bending Radius:** 3.250 inches **End Application:** Transport aircraft c-130 **Connection Style:** Swivel nut, flareless 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end Thready Qty Per Inch (tpi): 14 1st end **Burst Test Pressure:** 12000.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch **Thread Size:** 0.875 inches 1st end Seat Angle: 12.0 degrees 1st end **Hydrostatic Test Pressure:** 6000.0 pounds per square inch **Inside Surface Condition:** Smooth Measuring Method And Length: 46.000 inches working Media For Which Designed: Fuel/oil, hydrocarbon single response **Thread Series Designator:** Unjf 1st end

## NSN 4720-01-517-8415

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0

