

View Online at <https://aerobasegroup.com/nsn/4720-01-518-6755>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

1.101 inches

Temperature Rating:

275.0 degrees fahrenheit single response

Outside Diameter:

Between 1.560 inches and 1.650 inches

Minimum Inside Bending Radius:

12.000 inches

End Application:

Mount, super rapid gun, 76/62 mm.

Connection Style:

Swivel nut, flareless 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

12 2nd end

Burst Test Pressure:

12000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

1.625 inches 2nd end

Seat Angle:

12.0 degrees 2nd end

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

30.050 inches and 30.550 inches

Special Features:

Temperature rating is ; burst test pressure at high temperature is 9000.0 psi. ; can also be used in some pneumatic systems which allow some gaseous diffusion through hose wall

Media For Which Designed:

Hydraulic fluid single response

Thread Series Designator:

Unj 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A542a0