NSN 4720-01-519-1391

Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-519-1391

| view Online at https://aerobasegroup.com/hish/4/20-01-515-1591 |
|--|
| Cross Sectional Shape: |
| Round |
| Inside Diameter: |
| Between 0.212 inches and 0.250 inches |
| Tempurature Rating: |
| 400.0 degrees fahrenheit single response |
| Outside Diameter: |
| Between 0.650 inches and 0.660 inches |
| Minimum Inside Bending Radius: |
| 1.500 inches |
| End Application: |
| Nha hydraulic instl, v-22 aircraft |
| Connection Style: |
| Swivel, plain 2nd end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded external pipe 1st end |
| Burst Test Pressure: |
| 12000.0 pounds per square inch |
| Maximum Operating Pressure: |
| 6000.0 pounds per square inch |
| Flow Angle: |
| 90.0 degrees 2nd end |
| Criticality Code Justification: |
| Agav |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 31.000 inches working |
| Product Name: |
| Hose assembly, ptfe, cres reinforcement, dynamic beam seal, 3000 psi |
| Thread Series Designator: |
| Unjs 2nd end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A 5 40 - 0 |

A542a0