

View Online at <https://aerobasegroup.com/nsn/4720-01-522-6571>

Cross Sectional Shape:

Round

Inside Diameter:

0.375 inches

Temperature Rating:

-40.0 degrees celsius single response and 100.0 degrees celsius single response

Outside Diameter:

0.680 inches

Minimum Inside Bending Radius:

2.000 inches

End Application:

Wheeled tanker

Connection Style:

Swivel nut with loose or integral clinch sleeve 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

20000.0 pounds per square inch

Maximum Operating Pressure:

5000.0 pounds per square inch

Thread Size:

0.375 inches 1st end

Inside Surface Condition:

Smooth

Measuring Method And Length:

49.750 inches working

Inside Diameter Hose Accommodated:

0.375 inches 1st end

Product Name:

Hydraulic hose, no skive, abrasion resistant tough cover with female seal lok swivel straight short connectors

Special Features:

Hose weight 0.280 lbs per foot; hose construction inner tube of oil resistant nitrile-based synthetic rubber, two braids of high tensile steel wire reinforcement and an oil, weather and abrasion resistant black synthetic rubber; designed for use with petroleum base hydraulic fluids and lubricating oils within a temp range m40.0 c to 100.0 c; water, water/oil emulsion and water/glycol hydraulic fluids up to 85.0 c; air up to 70.0 c

Media For Which Designed:

Hydraulic fluid single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0