## NSN 4720-01-523-4660

96906-ms8000 government standard

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-523-4660

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
Between 0.615 inches and 0.645 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response
Outside Diameter:
Between 0.750 inches and 0.812 inches
Minimum Inside Bending Radius:
6.500 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
5000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
1.063 inches 1st end
Seat Angle:
37.0 degrees 1st end
Inside Surface Condition:
Smooth
Measuring Method And Length:
42.250 inches working
Media For Which Designed:
Fuel/oil, hydrocarbon single response and hydraulic fluid single response and water single response
Thread Series Designator:
Unj 1st end
Specification Data:

## NSN 4720-01-523-4660

Nonmetallic Hose Assembly - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0