Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-524-6593

С	ross Sectional Shape:
R	ound
T	hread Class:
3ł	o 1st end
Т	hread Direction:
R	ight-hand 1st end
In	side Diameter:
0.	212 inches
T	empurature Rating:
-6	5.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
0	utside Diameter:
B	etween 0.360 inches and 0.390 inches
Μ	inimum Inside Bending Radius:
1.	500 inches
E	nd Application:
С	I-415 aircraft
С	onnection Style:
S	wivel nut flare 2nd end
E	nd Connection Design:
Si	traight 1st end
С	onnection Type:
TI	nreaded internal tube 1st end
в	urst Test Pressure:
16	6000.0 pounds per square inch
Μ	aximum Operating Pressure:
30	000.0 pounds per square inch
T	hread Size:
0.	438 inches 1st end
S	eat Angle:
37	7.0 degrees 2nd end
FI	low Angle:
90	0.0 degrees 2nd end
In	side Surface Condition:
S	mooth
Μ	easuring Method And Length:
18	3.000 inches
P	roduct Name:
Н	ose assembly, tfe, high pressure
Т	hread Series Designator:
U	njf 1st end
S	helf Life:
N	/a

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0