

View Online at <https://aerobasegroup.com/nsn/4720-01-524-7685>

Cross Sectional Shape:

Round

Thread Class:

3a 2nd end

Thread Direction:

Right-hand 2nd end

Inside Diameter:

0.212 inches

Temperature Rating:

400.0 degrees fahrenheit single response

Outside Diameter:

0.400 inches

Minimum Inside Bending Radius:

1.500 inches

Angle Between Rigid Elbow Fittings In Deg:

180.0

Quick Disconnect Size:

0.250 inches 1st end

End Application:

Pressure switch

Connection Style:

Push (internal) 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded external tube 2nd end

Burst Test Pressure:

12000.0 pounds per square inch

Maximum Operating Pressure:

2000.0 pounds per square inch

Thread Size:

0.437 inches 2nd end

Seat Angle:

37.0 degrees 2nd end

Hydrostatic Test Pressure:

4500.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Criticality Code Justification:

Feat

Inside Surface Condition:

Smooth

Product Name:

Hose and fitting assembly

Special Features:

Weapon system essential; hose assembly with elbow and female quick disconnect attached; elbow joins tee assembly with flared and male quick disconnect connections; assembly has three connections; quick disconnects are self-sealing; includes lanyard

Thread Series Designator:

Unjf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A542a0