Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-526-1851

Cross Sectional Shape:	
Round	
hread Class:	
b 1st end	
Thread Direction:	
Right-hand 1st end	
nside Diameter:	
0.500 inches	
empurature Rating:	
65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response	e
Ainimum Inside Bending Radius:	
5.500 inches	
Connection Style:	
Swivel nut, inverted flare 2nd end	
End Connection Design:	
Straight 1st end	
Connection Type:	
hreaded internal tube 1st end	
Features Provided:	
Nuts drilled for lockwire	
hready Qty Per Inch (tpi):	
8 1st end	
Burst Test Pressure:	
6000.0 pounds per square inch	
ayer Composition And Location:	
st layer braided wire and outer layer spirally wrapped steel fabric	
laximum Operating Pressure:	
000.0 pounds per square inch	
hread Size:	
0.844 inches 2nd end	
Seat Angle:	
3.5 degrees 2nd end	
lydrostatic Test Pressure:	
000.0 pounds per square inch	
low Angle:	
0.0 degrees 2nd end	
nside Surface Condition:	
Smooth	
hread Series Designator:	
Jnj 2nd end	
Shelf Life:	
l/a	

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0