

View Online at <https://aerobasegroup.com/nsn/4720-01-526-4987>

**Cross Sectional Shape:**

Round

**Thread Class:**

2b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.625 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response

**Outside Diameter:**

0.940 inches

**Minimum Inside Bending Radius:**

4.000 inches

**End Application:**

Vds mast

**Connection Style:**

Swivel nut flare 2nd end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Thready Qty Per Inch (tpi):**

14 2nd end

**Burst Test Pressure:**

14500.0 pounds per square inch

**Layer Composition And Location:**

Outer layer polyester and 1st layer braided steel wire and 2nd layer braided steel wire

**Maximum Operating Pressure:**

3625.0 pounds per square inch

**Thread Size:**

0.875 inches 2nd end

**Seat Angle:**

37.0 degrees 2nd end

**Flow Angle:**

90.0 degrees 2nd end

**Criticality Code Justification:**

Feat

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

9.250 inches working

**Inside Diameter Hose Accommodated:**

0.625 inches 2nd end

**Outside Diameter Tube Accommodated:**

0.625 inches 2nd end

**Special Features:**

Weapon system essential; elastomeric core; clean and cap ends; attached marking plate

**Media For Which Designed:**

Air and hydraulic fluid single response

**Thread Series Designator:**

Unf 2nd end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0