Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-526-5297

view Online at https://aerobasegroup.com/hsi//4720-01-520-5287	
Cross Sectional Shape:	
Round	
Thread Class:	
2b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.500 inches	
Tempurature Rating:	
-70.0 degrees fahrenheit single response and 212.0 degrees fahrenheit single response	
Outside Diameter:	
0.890 inches	
Minimum Inside Bending Radius:	
3.500 inches	
Exterior Color:	
Black	
End Application:	
Vds mast	
Connection Style:	
Swivel nut, gasket seal 1st end	
End Connection Design:	
Straight 1st end	
End Fitting Component And Material:	
Complete fitting stainless steel all ends	
Connection Type:	
Threaded internal tube 1st end	
Thready Qty Per Inch (tpi):	
16 1st end	
Second End Relationship With First End:	
Identical	
Burst Test Pressure:	
12000.0 pounds per square inch	
First End Swivel Action Capability:	
Not included	
Layer Composition And Location:	
Outer layer polyester err-100	
Maximum Operating Pressure:	
3000.0 pounds per square inch	
Thread Size:	
0.812 inches 1st end	
Flow Angle:	
45.0 degrees 2nd end	

Nonmetallic Hose Assembly - Page 2 of 2



Criticality Code Justification:

Feat

Inside Surface Condition:

Smooth

Measuring Method And Length:

24.250 inches working

Special Features:

Weaponsystem essential; elastomeric core; clean and cap ends; attached marking plate

Media For Which Designed:

Air single response and hydraulic fluid single response

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0