

View Online at <https://aerobasegroup.com/nsn/4720-01-526-5907>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.375 inches

Temperature Rating:

-70.0 degrees fahrenheit single response and 212.0 degrees fahrenheit single response

Outside Diameter:

0.720 inches

Minimum Inside Bending Radius:

3.000 inches

Exterior Color:

Black

End Application:

Vds mast

Connection Style:

Swivel nut, gasket seal 1st end

End Connection Design:

Straight 2nd end

End Fitting Component And Material:

Complete fitting steel all ends

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

18 2nd end

Second End Relationship With First End:

Not identical

Burst Test Pressure:

12000.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer polyester err-100

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

0.687 inches 1st end

Criticality Code Justification:

Feat

Inside Surface Condition:

Smooth

Measuring Method And Length:

52.000 inches working

Second End Swivel Action Capability:

Not included

Special Features:

Weapon system essential; elastomeric core; clean and cap ends; attached marking plate

Media For Which Designed:

Air single response and hydraulic fluid single response

Thread Series Designator:

Uns 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0