Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-526-6340

Round Inside Diameter: 0.625 inches Tempurature Rating: -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response Minimum Inside Bending Radius: 6.000 inches End Application: Paint dispenser Connection Style: Push (external) 1st end End Connection Design: Straight 1st end Connection Type: External quick disconnect 1st end Burst Test Pressure: 6000.0 pounds per square inch Maximum Operating Pressure: 1500.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 16.000 inches Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:		tional Shape:
0.625 inches Tempurature Rating: -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response Minimum Inside Bending Radius: 6.000 inches End Application: Paint dispenser Connection Style: Push (external) 1st end End Connection Design: Straight 1st end Connection Type: External quick disconnect 1st end Burst Test Pressure: 6000.0 pounds per square inch Maximum Operating Pressure: 1500.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 16.000 inches Sheff Life: N/a Unit Of Measure: - Demilitarization: No Fig:		
Tempurature Rating: -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response Minimum Inside Bending Radius: 6.000 inches End Application: Paint dispenser Connection Style: Push (external) 1st end End Connection Design: Straight 1st end Connection Type: External quick disconnect 1st end Burst Test Pressure: 6000.0 pounds per square inch Maximum Operating Pressure: 1500.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 16.000 inches Sheff Life: N/a Unit Of Measure: - Demilitarization: No Fig:		
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response Minimum Inside Bending Radius: 6.000 inches End Application: Paint dispenser Connection Style: Push (external) 1st end End Connection Design: Straight 1st end Connection Type: External quick disconnect 1st end Burst Test Pressure: 6000.0 pounds per square inch Maximum Operating Pressure: 1500.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 16.000 inches Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:		
Minimun Inside Bending Radius:6.000 inchesEnd Application:Paint dispenserConnection Style:Push (external) 1st endEnd Connection Design:Straight 1st endConnection Type:External quick disconnect 1st endBurst Test Pressure:6000.0 pounds per square inchMaximum Operating Pressure:1500.0 pounds per square inchMaximum Operating Pressure:1500.0 pounds per square inchBurst Test Condition:SmoothMeasuring Method And Length:16.000 inchesShelf Life:N/aUnit Of Measure:-Penilitarization:NoFig:		
6.000 inches End Application: Paint dispenser Connection Style: Push (external) 1st end End Connection Design: Straight 1st end Connection Type: External quick disconnect 1st end Burst Test Pressure: 6000.0 pounds per square inch Maximum Operating Pressure: 1500.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 16.000 inches Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:		
End Application: Paint dispenser Connection Style: Push (external) 1st end End Connection Design: Straight 1st end Connection Type: External quick disconnect 1st end Burst Test Pressure: 6000.0 pounds per square inch Maximum Operating Pressure: 1500.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 16.000 inches Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:		-
Paint dispenser Connection Style: Push (external) 1st end End Connection Design: Straight 1st end Connection Type: External quick disconnect 1st end Burst Test Pressure: 6000.0 pounds per square inch Maximum Operating Pressure: 1500.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 16.000 inches Shelf Life: N/a Unit Of Measure:  Demilitarization: No		
Connection Style: Push (external) 1st end End Connection Design: Straight 1st end Connection Type: External quick disconnect 1st end Burst Test Pressure: 6000.0 pounds per square inch Maximum Operating Pressure: 1500.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 16.000 inches Shelf Life: N/a Unit Of Measure:		
Push (external) 1st end End Connection Design: Straight 1st end Connection Type: External quick disconnect 1st end Burst Test Pressure: 6000.0 pounds per square inch Maximum Operating Pressure: 1500.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 16.000 inches Shelf Life: N/a Unit Of Measure:  Demilitarization: No	-	
End Connection Design: Straight 1st end Connection Type: External quick disconnect 1st end Burst Test Pressure: 6000.0 pounds per square inch Maximum Operating Pressure: 1500.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 16.000 inches Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:		-
Straight 1st end Connection Type: External quick disconnect 1st end Burst Test Pressure: 6000.0 pounds per square inch Maximum Operating Pressure: 1500.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 16.000 inches Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:		
Connection Type: External quick disconnect 1st end Burst Test Pressure: 6000.0 pounds per square inch Maximum Operating Pressure: 1500.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 16.000 inches Shelf Life: N/a Unit Of Measure:  Demilitarization: No		-
External quick disconnect 1st end Burst Test Pressure: 6000.0 pounds per square inch Maximum Operating Pressure: 1500.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 16.000 inches Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	-	
Burst Test Pressure: 6000.0 pounds per square inch Maximum Operating Pressure: 1500.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 16.000 inches Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:		
6000.0 pounds per square inch Maximum Operating Pressure: 1500.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 16.000 inches Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	-	
Maximum Operating Pressure:1500.0 pounds per square inchInside Surface Condition:SmoothMeasuring Method And Length:16.000 inchesShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:		
1500.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 16.000 inches Shelf Life: N/a Unit Of Measure:  Demilitarization: No		
Inside Surface Condition: Smooth Measuring Method And Length: 16.000 inches Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:		
Smooth Measuring Method And Length: 16.000 inches Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	-	
Measuring Method And Length: 16.000 inches Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:		face Condition:
16.000 inches Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:		
Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	-	-
N/a Unit Of Measure:  Demilitarization: No Fiig:		
Unit Of Measure:  Demilitarization: No Fiig:		
 Demilitarization: No Fiig:		
No Fiig:	Unit Of Me	asure:
No Fiig:		
Fiig:		cation:
-		
	Fiig: A542a0	