Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-526-6445

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.500 inches
Tempurature Rating:
-70.0 degrees fahrenheit and 212.0 degrees fahrenheit single response
Outside Diameter:
0.890 inches
Minimum Inside Bending Radius:
3.500 inches
Exterior Color:
Black
End Application:
Vds mast
Connection Style:
Swivel nut, gasket seal 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
16 2nd end
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
1st layer braided fiber and outer layer polyester
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.812 inches 2nd end
Criticality Code Justification:
Feat
Inside Surface Condition:
Smooth
Measuring Method And Length:
35.500 inches working
Special Features:
Weapon system essential; elastomeric core; clean and cap ends; attached marking plate



Media For Which Designed:

Air and hydraulic fluid single response

Thread Series Designator:

Un 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0