

View Online at <https://aerobasegroup.com/nsn/4720-01-527-5042>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.625 inches

Temperature Rating:

-40.0 degrees fahrenheit and 158.0 degrees fahrenheit single response

Outside Diameter:

0.960 inches

Minimum Inside Bending Radius:

2.500 inches

Exterior Color:

Black

End Application:

Fuel/electric/air brake

Connection Style:

Swivel nut flare 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

12 2nd end

Burst Test Pressure:

1800.0 pounds per square inch

Layer Composition And Location:

Outer layer braided synthetic cord and 1st layer braided fiber and 2nd layer molded rubber, synthetic

Maximum Operating Pressure:

450.0 pounds per square inch

Thread Size:

1.062 inches 2nd end

Seat Angle:

37.0 degrees 2nd end

Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Abrasion resistant and oil resistant and weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

35.250 inches working

Special Features:

Nylon fiber outer braid; stainless steel fittings; short drop elbow

Media For Which Designed:

Air single response

Thread Series Designator:

Un 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0