Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-529-0041

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-40.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response
Outside Diameter:
0.790 inches
Minimum Inside Bending Radius:
5.000 inches
End Application:
Hydraulic power unit
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting stainless steel all ends
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Second End Relationship With First End:
Identical
Burst Test Pressure:
22000.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
Outer layer wrapped rubber, synthetic err-100
Maximum Operating Pressure:
5500.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Seat Angle:
37.0 degrees 1st end
Inside Surface Condition:
Smooth



Measuring Method And Length: 28.000 inches **Special Features:** Stainless steel fitting; fc136 hose Media For Which Designed: Hydraulic fluid single response **Thread Series Designator:** Unf 1st end Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A542a0