NSN 4720-01-529-3298



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-529-3298 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.375 inches **Tempurature Rating:** -70.0 degrees fahrenheit and 212.0 degrees fahrenheit single response **Outside Diameter:** 0.720 inches **Minimum Inside Bending Radius:** 3.000 inches **Exterior Color:** Black Angle Between Rigid Elbow Fittings In Deg: 15.0 **End Application:** Propulsion section **Connection Style:** Swivel nut, gasket seal 1st end **End Connection Design:** Elbow 1st end **Connection Type:** Threaded internal tube 1st end Thready Qty Per Inch (tpi): 16 1st end **Burst Test Pressure:** 12000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided fiber and outer layer polyester **Maximum Operating Pressure:** 3000.0 pounds per square inch **Thread Size:** 0.688 inches 1st end Flow Angle: 45.0 degrees 1st end **Criticality Code Justification:**

Feat **Inside Surface Condition:**

Smooth

NSN 4720-01-529-3298

No Fiig: A542a0

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length: 45.250 inches working Special Features: Weaponsystem essential; elastomeric core; clean and cap ends; attached marking plate Media For Which Designed: Air and hydraulic fluid single response Thread Series Designator: Un 1st end Shelf Life: N/a Unit Of Measure: --Demilitarization: